

GARMIN Ltd. or its subsidiaries
c/o GARMIN International, Inc.
1200 E. 151st Street
Olathe, Kansas 66062 U.S.A.

FAA APPROVED AIRPLANE FLIGHT MANUAL SUPPLEMENT

GFC 500 Autopilot with ESP

Installed in

**Textron Aviation 182E / 182F / 182G / 182H / 182J / 182K / 182L / 182M /
182N / 182P / 182Q / 182R / 182S / 182T / T182 / T182T**

And

Cessna F182P / F182Q

Dwg. Number: 190-02291-06 Rev. 1

This Supplement must be attached to the FAA Approved Airplane Flight Manual when the GFC 500 Autopilot system is installed in accordance with STC SA01866WI. The information contained herein supplements the information of the basic Airplane Flight Manual. For Limitations, Procedures, and Performance information not contained in this Supplement consult the basic Pilot's Operating Handbook and FAA Approved Airplane Flight Manual.

Airplane Serial Number: _____

Airplane Registration Number: _____

FAA Approved By:  _____

Robert G. Murray
ODA STC Unit Administrator
Garmin International, Inc
ODA-240087-CE

Date: 12/21/2017

© Copyright 2017
Garmin Ltd. or its subsidiaries
All Rights Reserved

Except as expressly provided herein, no part of this manual may be reproduced, copied, transmitted, disseminated, downloaded or stored in any storage medium, for any purpose without the express prior written consent of Garmin. Garmin hereby grants permission to download a single copy of this manual and of any revision to this manual onto a hard drive or other electronic storage medium to be viewed and to print one copy of this manual or of any revision hereto, provided that such electronic or printed copy of this manual or revision must contain the complete text of this copyright notice and provided further that any unauthorized commercial distribution of this manual or any revision hereto is strictly prohibited.

Garmin International, Inc.
1200 E. 151st Street
Olathe, KS 66062 USA
Telephone: 913-397-8200
www.garmin.com

Garmin International, Inc

Log of Revisions

FAA APPROVED AIRPLANE FLIGHT MANUAL SUPPLEMENT

GFC 500 Autopilot with ESP

Installed in

**Textron Aviation 182E / 182F / 182G / 182H / 182J / 182K / 182L / 182M /
182N / 182P / 182Q / 182R / 182S / 182T / T182 / T182T**

And

Cessna F182P / F182Q

REV NO.	PAGE NO(S)	DESCRIPTION	DATE OF APPROVAL	FAA APPROVED
1	ALL	Original Issue	See Cover	See Cover

This page intentionally left blank.

Table of Contents

Section 1 – General	1-1
USE OF THE SUPPLEMENT	1-1
ABBREVIATIONS AND TERMINOLOGY	1-2
INSTALLED EQUIPMENT INTERFACES	1-3
INSTALLED FEATURES CHECKLIST	1-4
Section 2 – Limitations	2-1
Section 3 – Emergency Procedures	3-1
AUTOPILOT MALFUNCTION / PITCH TRIM RUNAWAY	3-1
AUTOPILOT FAILURE / ABNORMAL DISCONNECT	3-2
PITCH TRIM FAILURE	3-2
ESP ACTIVATION	3-2
OVERSPEED PROTECTION (MAXSPD)	3-3
UNDERSPEED PROTECTION (MINSPD)	3-3
Section 3A – Non-Normal Procedures	3-5
AUTOPILOT ABNORMAL DISCONNECT	3-5
AUTOPILOT PRE-FLIGHT TEST FAIL	3-5
LOSS OF NAVIGATION INFORMATION	3-5
LOSS OF AIRSPEED DATA	3-6
LOSS OF ALTITUDE DATA	3-6
LOSS OF GPS INFORMATION	3-6
HEADING DATA SOURCE FAILURE	3-7
ELEVATOR MISTRIM (AUTOTRIM)	3-7
Section 4 – Normal Procedures	4-1
GFC 500 POWER UP	4-1
FLIGHT DIRECTOR / AUTOPILOT NORMAL OPERATING PROCEDURES	4-1
MANUAL AUTOPILOT DISCONNECT	4-1
VERTICAL MODES	4-2
VERTICAL SPEED (VS) MODE	4-2
INDICATED AIRSPEED (IAS) MODE	4-2
ALTITUDE HOLD (ALT) MODE, MANUAL CAPTURE	4-2
GO AROUND.....	4-2
MANUAL PITCH TRIM WITH AUTOPILOT ENGAGED	4-3
LATERAL MODES	4-4
HEADING MODE (HDG)	4-4
TRACK MODE (TRK)	4-4

NAVIGATION (VOR).....	4-4
NAVIGATION (GPS).....	4-5
APPROACHES	4-6
ILS APPROACH	4-6
LOC APPROACH (GS out).....	4-7
GPS APPROACH (LPV, LNAV/VNAV, LP+V, or LNAV+V)	4-7
GPS APPROACH (LP, LNAV).....	4-8
LOC BC APPROACH	4-8
VOR APPROACH.....	4-9
DISABLING ESP.....	4-10
Section 5 – Performance	5-1
Section 6 – Weight and Balance	6-1
Section 7 – System Description.....	7-1
AFCS OVERVIEW	7-1
AUTOPILOT CONTROL UNIT AND DISPLAY	7-4
PREFLIGHT TEST	7-7
MESSAGES AND ANNUNCIATIONS	7-7
LIGHTING.....	7-8

SECTION 1 – GENERAL

The information in this supplement is FAA-approved material and must be attached to the Pilot's Operating Handbook and FAA Approved Airplane Flight Manual (POH/AFM) when the airplane has been modified by installation of the Garmin GFC 500 Autopilot system in accordance with Garmin International, Inc. approved data.

The information in this supplement supersedes or adds to the basic POH/AFM only as set forth below. Users of the manual are advised to always refer to the supplement for possibly superseding information and placarding applicable to operation of the airplane.

USE OF THE SUPPLEMENT

The following definitions apply to WARNINGS, CAUTIONS and NOTES found throughout the supplement:

WARNING

Operating procedures, techniques, etc., which may result in personal injury or loss of life if not carefully followed.

CAUTION

Operating procedures, techniques, etc., which may result in damage to equipment if not carefully followed.

NOTE

Operating procedures, techniques, etc., which is considered essential to emphasize.

ABBREVIATIONS AND TERMINOLOGY

The following glossary is applicable within the airplane flight manual supplement

AFCS	Automatic Flight Control System	LNAV/VNAV	Lateral Navigation / Vertical Navigation Approach
AFM	Airplane Flight Manual	LOC	Localizer (no glideslope available)
AFMS	Airplane Flight Manual Supplement	LP	Localizer Performance
AGL	Above Ground Level	LP+V	Localizer Performance with Advisory Vertical Guidance
AHRS	Attitude and Heading Reference System	LPV	Localizer Performance with Vertical Guidance
ALT	Altitude	LVL	Level
AP	Autopilot	MDA	Minimum Descent Altitude
APR	Approach	PFT	Preflight Test
ATC	Air Traffic Control	POH	Pilot's Operating Handbook
BC	Back Course Approach	STC	Supplemental Type Certificate
CDI	Course Deviation Indicator	TO	Takeoff
DA	Decision Altitude	TRK	Track
DISC	Disconnect	VHF	Very High Frequency
DWG	Drawing	VOR	VHF Omni-directional Range
ESP	Electronic Stability and Protection	VS	Vertical Speed
FAA	Federal Aviation Administration		
FAF	Final Approach Fix		
FD	Flight Director		
GA	Go Around		
GFC 500	Garmin Autopilot		
GMC 507	Autopilot Mode Control Panel		
GNSS	Global Navigation Satellite System		
GPS	Global Positioning System		
GS	Glideslope		
GSA	Garmin Servo Actuator		
HDG	AFCS heading mode		
IAS	Indicated Airspeed		
ILS	Instrument Landing System		
INT	Interrupt		
KIAS	Knots Indicated Airspeed		
LNAV	Lateral Navigation		
LNAV+V	Lateral Navigation with Advisory Vertical Guidance		

INSTALLED EQUIPMENT INTERFACES

The following is the list of installed equipment and functions associated with the GFC 500 Autopilot installation in this airplane.

Table 1-1: Table of Installed Equipment Interfaces

DEVICE TYPE	Manufacturer / Model If not installed, note N/A	Additional Information
GPS Navigator #1		Is Navigator #1 interfaced to GFC 500? <input type="checkbox"/> YES <input type="checkbox"/> NO
VHF Nav Radio #1		Is VHF Nav Radio #1 interfaced to GFC 500? <input type="checkbox"/> YES <input type="checkbox"/> NO
VHF Nav Radio #2		
Pitch Trim Servo		

INSTALLED FEATURES CHECKLIST

The checked autopilot modes and features are available on this aircraft.

Basic AP Features

- Flight Director
- Electric Pitch Trim
- Overspeed Protection
- Underspeed Protection

Electronic Stability and Protection

- Pitch/Roll Attitude
- High Speed Protection
- Low Speed Protection

Vertical Autopilot Modes

- Pitch (PIT)
- Level (Zero vertical speed)
- Go Around (GA)
- Altitude Hold
- Vertical Speed
- Altitude Capture via Altitude Preselect
- Indicated Airspeed (IAS)
- GPS Approach Glidepath
- ILS Glideslope

Lateral Autopilot Modes

- Roll (ROL)
- Level (Wings Level)
- Go Around (GA)
- Heading
- Track
- GPS Navigation
- VHF Navigation
- Approach Mode
 - GPS
 - VOR/LOC

SECTION 2 – LIMITATIONS

The Garmin G5 Electronic Flight Instrument Pilot's Guide for Certified Aircraft, part number 190-01112-12 Rev A (or later approved revisions), must be immediately available to the flight crew.

This AFMS is applicable to the software versions shown below:

Software Item	Software Version (or later FAA Approved version for this STC)
G5 Software Version	5.0

A pilot must be seated in the left pilot's seat, with seatbelt fastened, during all autopilot operations.

Do not use autopilot during takeoff and landing.

The GFC 500 AFCS preflight test must complete successfully prior to use of the autopilot, flight director or manual electric trim.

The maximum fuel imbalance with the autopilot engaged is 10 gallons.

Autopilot maximum engagement speed is 165 KIAS.

The autopilot must be disengaged below 200 feet AGL during approach operations and below 800 feet AGL during all other operations.

The GFC 500 autopilot is approved for Category 1 precision approaches and non-precision approaches only.

This page intentionally left blank.

SECTION 3 – EMERGENCY PROCEDURES

Some emergency situations require immediate memorized corrective action. These steps are printed in bold in the emergency procedures and should be accomplished without the aid of the checklist.

AUTOPILOT MALFUNCTION / PITCH TRIM RUNAWAY

If the airplane deviates unexpectedly from the planned flight path:

1. **Control Wheel**.....**GRIP FIRMLY**
2. **AP DISC / TRIM INT Button****PRESS AND HOLD**

CAUTION

Be prepared for high elevator control forces.

3. **Aircraft Attitude**.....**MAINTAIN / REGAIN AIRCRAFT CONTROL**
4. Elevator Trim..... **RE-TRIM** if necessary using Elevator Tab Wheel
5. AUTOPILOT Circuit Breaker..... **PULL**

NOTE

Do not release the AP DISC / TRIM INT Button until after pulling the AUTOPILOT Circuit Breaker.

Pulling the AUTOPILOT circuit breaker will render the autopilot and ESP inoperative.

6. AP DISC / TRIM INT Button..... **RELEASE**

WARNING

In flight, do not overpower the autopilot. The trim will operate in the direction opposing the overpower force, which will result in large out-of-trim forces.

Do not attempt to re-engage the autopilot or use manual electric pitch trim until the cause of the malfunction has been corrected.

AUTOPILOT FAILURE / ABNORMAL DISCONNECT

(Red AP in autopilot status box on display, continuous aural disconnect tone.)

1. AP DISC / TRIM INT Button or G5 Knob PRESS AND RELEASE
(to cancel disconnect tone)
2. Aircraft Attitude..... MAINTAIN / REGAIN AIRCRAFT CONTROL

NOTE

The autopilot disconnect may be accompanied by a red AFCS in the autopilot status box, indicating the automatic flight control system has failed. The flight director will not be available and the autopilot cannot be re-engaged with this annunciation present.

If the disconnect is accompanied by an amber AP with a red X, the autopilot will not be available however the flight director will still be functional.

In the event of a GMC failure, pressing the G5 knob will acknowledge the disconnect tone.

PITCH TRIM FAILURE

(Red PTRIM on G5 display.)

This failure will only occur if the optional pitch trim servo is installed.

1. Indicates a failure of the pitch trim servo.
2. Control Wheel GRIP FIRMLY
3. AP DISC / TRIM INT Button..... PRESS and RELEASE
(Be prepared for high elevator control forces)
4. Elevator Trim..... AS REQUIRED USING ELEVATOR TAB WHEEL

NOTE

The autopilot may be re-engaged. Refer to the normal procedures section of this AFMS, MANUAL PITCH TRIM WITH AUTOPILOT ENGAGED.

ESP ACTIVATION

1. Throttle AS REQUIRED
2. Aircraft Attitude..... MAINTAIN / REGAIN AIRCRAFT CONTROL

NOTE

If ESP is active for approximately 10 seconds, the autopilot will automatically engage in LVL mode, an aural 'ENGAGING AUTOPILOT' will be played, (or a Sonalert tone will sound for installations without a supported audio panel) and the autopilot will roll the wings level and fly at zero-vertical speed. Refer to Section 7, System Description for further information.

ESP will be disabled by pressing and holding the AP DISC / TRIM INT button. Releasing the button will allow ESP to function.

OVERSPEED PROTECTION (MAXSPD)

(MAXSPD displayed on G5, AIRSPEED – AIRSPEED Aural sounds.)

1. **Throttle** **REDUCE**
2. **Aircraft Attitude and Altitude** **MONITOR**

After overspeed condition is corrected:

3. Autopilot RESELECT VERTICAL AND LATERAL MODES (if necessary)
4. Throttle ADJUST as necessary

NOTE

Overspeed protection mode provides a pitch up command to decelerate the airplane at or below the maximum autopilot operating speed.

UNDERSPEED PROTECTION (MINSPD)

(MINSPD displayed on G5, AIRSPEED – AIRSPEED Aural sounds.)

1. **Throttle** **INCREASE POWER AS REQUIRED TO CORRECT UNDERSPEED**
2. **Aircraft Attitude and Altitude** **MONITOR**

After underspeed condition is corrected:

3. Autopilot RESELECT VERTICAL AND LATERAL MODES (if necessary)
4. Throttle ADJUST as necessary

NOTE

Autopilot Underspeed Protection Mode provides a pitch down command to maintain 65 KIAS.

This page intentionally left blank.

SECTION 3A – NON-NORMAL PROCEDURES

AUTOPILOT ABNORMAL DISCONNECT

(Red AP in the G5 autopilot status box, continuous aural disconnect tone.)

1. AP DISC / TRIM INT Button.....PRESS AND RELEASE
(to cancel disconnect tone)
2. Aircraft Attitude..... MAINTAIN / REGAIN AIRCRAFT CONTROL

NOTE

The autopilot disconnect may be accompanied by a red AFCS in the autopilot status box, indicating the automatic flight control system has failed. The flight director will not be available and the autopilot cannot be re-engaged with this annunciation present.

If the disconnect is accompanied by an amber AP with a red X, the autopilot will not be available however the flight director will still be functional.

AUTOPILOT PRE-FLIGHT TEST FAIL

(Amber AP with a red X in G5 autopilot status box.)

1. Indicates the AFCS system failed the automatic Pre-Flight test.

NOTE

The autopilot, ESP, and electric elevator trim are inoperative. Flight director will still function.

LOSS OF NAVIGATION INFORMATION

(Amber GPS, VOR, LOC, or BC flashes for 10 seconds on G5.)

NOTE

If a navigation signal is lost while the autopilot is tracking it, the autopilot will roll the aircraft wings level and default to roll mode (ROL).

1. GMC 507 Mode Panel..... SELECT HDG mode and SET desired heading
2. NAV Source SELECT a valid NAV source
3. NAV Key..... PRESS

If on an instrument approach at the time the navigation signal is lost:

4. Missed Approach Procedure..... EXECUTE (as applicable)

LOSS OF AIRSPEED DATA

(Red X through airspeed tape on the G5 display, amber AP with a red X in autopilot status box.)

NOTE

If airspeed data is lost while the autopilot is tracking airspeed, the flight director will default to pitch mode (PIT).

1. AP DISC / TRIM INT Button..... PRESS AND RELEASE
(to cancel disconnect tone)
2. Aircraft Attitude..... MAINTAIN / REGAIN AIRCRAFT CONTROL
3. Manual Elevator Trim..... TRIM as required

NOTE

The autopilot cannot be re-engaged. The flight director is available however IAS mode cannot be selected. Loss of airspeed will be accompanied by a red PTRIM indication on the G5 (if a pitch trim servo is installed).

LOSS OF ALTITUDE DATA

(Red X through altitude tape on the G5 display.)

NOTE

If altitude data is lost while the autopilot is tracking altitude, the autopilot will default to pitch mode (PIT).

1. Autopilot SELECT different vertical mode

LOSS OF GPS INFORMATION

(GPS position information is lost to the autopilot.)

NOTE

If GPS position data is lost while the autopilot is tracking a GPS, VOR, LOC or BC course, the autopilot will default to roll mode (ROL). The autopilot will default to pitch mode if GPS information is lost while tracking an ILS. The autopilot uses GPS aiding in VOR, LOC and BC modes.

1. AutopilotSELECT different lateral and vertical mode (as necessary)

If on an instrument approach:

- AP DISC / TRIM INT buttonPRESS, Continue the approach manually
Or
- Missed Approach Procedure..... EXECUTE (as applicable)

HEADING DATA SOURCE FAILURE

1. Autopilot SELECT different lateral mode

NOTE

Without a heading source to the navigator, the following features will not operate:

- GPSS will not be provided to the autopilot for heading legs.
- Map cannot be oriented to Heading Up.
- Track information will be displayed on the G5.

ELEVATOR MISTRIM (AUTOTRIM)

(Amber TRIM UP or TRIM DOWN displayed on the G5.)

WARNING

Do not attempt to overpower the autopilot in the event of a pitch mistrim. The autopilot servo will oppose pilot input and will cause pitch trim to run opposite the direction of pilot input. This will lead to a significant out-of-trim condition, resulting in large control wheel force when disengaging the autopilot.

NOTE

Indicates a mistrim of the elevator while the autopilot is engaged.

If a pitch trim servo is not installed, refer to the normal procedures section of this AFMS, MANUAL PITCH TRIM WITH AUTOPILOT ENGAGED. If a pitch trim servo is installed, the autopilot will normally trim the airplane as required. However, during rapid acceleration, deceleration, configuration changes, or near either end of the elevator trim limits, momentary illumination of this message may occur. If the autopilot is disconnected while this message is displayed, high elevator control forces are possible.

If a pitch trim servo is not installed:

1. Refer to the normal procedures section of this AFMS, MANUAL PITCH TRIM WITH AUTOPILOT ENGAGED.

If a pitch trim servo is installed:

NOTE

Momentary display of the TRIM UP or TRIM DOWN message during configuration changes or large airspeed changes is normal.

1. Control Wheel GRIP FIRMLY

WARNING

Be prepared for significant sustained control forces in the direction of the mistrim annunciation. For example, TRIM DOWN indicates nose down control wheel force will be required upon autopilot disconnect.

2. AP DISC / TRIM INT Button..... PRESS AND RELEASE
3. Manual Elevator Trim RE-TRIM as required

Electric pitch trim should be considered inoperative until the cause of the mistrim has been investigated and corrected.

SECTION 4 – NORMAL PROCEDURES

GFC 500 POWER UP

During the preflight test the G5 will display PFT in the autopilot status box. The autopilot disconnect tone sounds at the completion of the preflight test. When the GFC 500 passes preflight test, PFT will be removed from the autopilot status box.

FLIGHT DIRECTOR / AUTOPILOT NORMAL OPERATING PROCEDURES

Autopilot/Flight Director mode annunciations are displayed at the top of the G5 Electronic Flight Instrument. Green text indicates active autopilot/flight director modes. Armed modes are indicated in white text. Normal mode transitions will flash inverse video for 10 seconds before becoming steady. Abnormal mode transitions will flash for 10 seconds in amber text before the default mode is annunciated as the active mode in green text. Default autopilot/flight director modes are Roll (ROL) and Pitch (PIT) modes.

The autopilot status box displays the autopilot engagement status as well as armed and active flight director modes.

Autopilot Engagement with Flight Director Off — Upon engagement, the autopilot will be set to hold the current attitude of the airplane if the flight director was not previously on. In this case, 'ROL' and 'PIT' will be annunciated.

Autopilot Engagement with Flight Director On — If the flight director is on, the autopilot will smoothly pitch and roll the airplane to capture the FD command bars. The prior flight director modes remain unchanged.

Autopilot Disengagement — The most common way to disconnect the autopilot is to press and release the AP DISC / TRIM INT button located on the control yoke. An autopilot disconnect tone will sound and an amber AP will be annunciated on the G5 autopilot status box. Other ways to disconnect the autopilot include:

- Pressing the AP Key on the GMC 507 Mode Controller
- Operating the Electric Pitch Trim Switch (located on the control wheel)
- Pulling the AUTOPILOT circuit breaker

In the event of unexpected autopilot behavior, press and holding the AP DISC / TRIM INT button will disconnect the autopilot and remove all power to the servos.

MANUAL AUTOPILOT DISCONNECT

If necessary, the autopilot may be manually disconnected using any one of the following methods:

1. AP DISC / TRIM INT Button..... PRESS and RELEASE
(Pilot's control wheel)
2. AP KeyPRESS
3. Pitch Trim Switch ACTIVATE
4. AUTOPILOT Circuit Breaker PULL

VERTICAL MODES

VERTICAL SPEED (VS) MODE

1. Altitude Preselect SET to Desired Altitude
2. Press VS Key, autopilot synchronizes to the airplane's current vertical speed.
3. Vertical Speed ReferenceADJUST using UP / DN Wheel
4. Green ALT..... VERIFY Upon Altitude Capture

INDICATED AIRSPEED (IAS) MODE

1. Altitude Preselect SET to Desired Altitude
2. Press IAS Key, autopilot synchronizes to the airplane's current indicated airspeed.
3. AIRSPEED ReferenceADJUST using UP / DN Wheel
4. Throttle ADJUST, INCREASE POWER to climb
DECREASE POWER to descend
5. Green ALT..... VERIFY Upon Altitude Capture

ALTITUDE HOLD (ALT) MODE, MANUAL CAPTURE

1. When at the desired altitudePRESS ALT key

NOTE

If climbing or descending at a high rate when the ALT key is pressed, the airplane will overshoot the reference altitude and then return to it. The amount of overshoot will depend on the vertical speed when the ALT key is pressed.

The altitude reference is displayed in the autopilot status box. The reference may be changed by +/- 200 FT using the UP / DN wheel.

GO AROUND

1. GO AROUND button PRESS – Verify GA / GA on G5
autopilot will not disengage
2. Autopilot (if engaged)VERIFY airplane pitches up following flight director command bars
3. Throttle APPLY Go Around power
4. GMC 507 Mode Panel.....PRESS NAV to couple to selected navigation source
OR
PRESS HDG to Fly ATC Assigned Missed Approach Heading
5. Altitude Preselect VERIFY
Set to appropriate altitude.

NOTE

The pilot is responsible for initial missed approach guidance in accordance with published procedure. When the GA button is pressed the Flight Director command bars will command go-around pitch attitude and wings level. The pilot must select the CDI to the appropriate navigation source and select the desired lateral and vertical flight director modes.

MANUAL PITCH TRIM WITH AUTOPILOT ENGAGED

(Amber TRIM UP or TRIM DOWN displayed on G5.)

NOTE

If the aircraft is not equipped with a pitch trim servo, the pilot must manually adjust the pitch trim when airspeed and aircraft configuration changes are made.

A message will be displayed on the G5 display to indicate the pitch servo is holding sustained force, and the pilot must manually trim the aircraft.

1. If TRIM UP message is displayed.....MANUALLY TRIM nose up
2. If TRIM DOWN message is displayed MANUALLY TRIM nose down

LATERAL MODES

HEADING MODE (HDG)

1. HDG KeyPRESS
The autopilot will turn the airplane in the direction of the heading bug.
2. HDG/TRK Knob..... Rotate to set heading bug to desired heading.

NOTE

If heading bug is reset too quickly, the airplane could turn in the opposite direction as the heading bug's movement.

TRACK MODE (TRK)

1. TRK KeyPRESS
The autopilot will turn the airplane in the direction of the track bug.
2. HDG/TRK Knob..... Rotate to set track bug to desired track.

NOTE

If track bug is reset too quickly, the airplane could turn in the opposite direction as the track bug's movement.

NAVIGATION (VOR)

1. Navigation Source.SELECT CDI to VHF NAV
Tune and identify the station frequency.
2. Course PointerSET CDI to the Desired Course
3. Intercept Heading ESTABLISH in HDG, TRK or ROL mode
4. NAV Key.....PRESS

NOTE

If the Course Deviation Indicator (CDI) is greater than one dot from center, the autopilot will arm the VOR mode. The pilot must ensure that the current heading will result in a capture of the selected course. If the CDI is one dot or less from center, the autopilot will enter the capture mode when the NAV key is pressed.

NAVIGATION (GPS)

1. Navigation Source..... SELECT CDI to GPS
2. Waypoint SELECT on Navigation Source
3. Course Pointer VERIFY CDI set to the Desired Course
4. Intercept Heading..... ESTABLISH in HDG or ROL mode
5. NAV Key..... PRESS

NOTE

If the Course Deviation Indicator (CDI) is greater than one dot from center, the autopilot will arm the GPS mode. The pilot must ensure that the current heading will result in a capture of the selected course. If the CDI is one dot or less from center, the autopilot will enter the capture mode when the NAV key is pressed.

APPROACHES

ILS APPROACH

1. Navigation Source..... SELECT CDI to VHF Nav
Tune and Identify an ILS station frequency.
2. CDI SET to front LOC course

NOTE

Ensure that the current heading will result in a capture of the selected course.

3. APR Key PRESS, verify LOC and GS ARMED
4. LOC and GS Mode..... VERIFY airplane Captures and Tracks LOC and GS
5. Missed Approach Altitude SET in Altitude preselect.

At Decision Altitude (DA),

6. AP DISC / TRIM INT button PRESS, Continue visually for a normal landing
Or
7. GO AROUND (GA) button PRESS, Execute Missed Approach Procedure
8. Apply GA power.

NOTE

Pressing the GA button will not disconnect the autopilot. Select NAV or HDG mode to fly the missed approach procedure.

If the Course Deviation Indicator (CDI) is greater than half scale deflection, the autopilot will arm the LOC mode. The pilot must ensure that the current heading will result in a capture of the selected course. If the CDI is within half scale deflection, the autopilot will enter the capture mode when the APR key is pressed.

When the selected navigation source is an ILS, glideslope coupling is automatically armed when the APR key is pressed. The glideslope cannot be captured until the localizer is captured. The autopilot can capture the glideslope from above or below the glideslope.

LOC APPROACH (GS out)

1. Navigation Source..... SELECT CDI to VHF Nav
Tune and Identify an ILS station frequency.
2. Course Pointer SET to front LOC course

NOTE

Ensure that the current heading will result in a capture of the selected course.

3. NAV Key.....PRESS, verify LOC ARMED
4. LOC Mode..... VERIFY airplane Captures and Tracks LOC Course
5. Altitude PreselectSET to next required step down altitude
6. Missed Approach AltitudeSET when in ALT mode at the MDA

At Missed Approach Point,

7. AP DISC / TRIM INT button PRESS, Continue visually for a normal landing
Or
8. GO AROUND (GA) button PRESS, Execute Missed Approach Procedure
9. Apply GA power.

NOTE

Pressing the GA button will not disconnect the autopilot. Select NAV or HDG mode to fly the missed approach procedure.

GPS APPROACH (LPV, LNAV/VNAV, LP+V, or LNAV+V)

1. Navigation Source..... SELECT CDI to GPS
2. Course PointerVERIFY CDI set to the Desired Course

NOTE

Ensure that the current heading will result in a capture of the selected course.

3. APR Key..... PRESS, verify GPS and GP ARMED
4. GPS and GP ModeVERIFY airplane Captures and Tracks GPS and GP
5. ALT KeyPRESS to level off at the MDA for a LP+V or LNAV+V approach

At DA (LPV or LNAV/VNAV approach), or MDA and Missed Approach Point (LP+V or LNAV+V),

6. AP DISC / TRIM INT button PRESS, Continue visually for a normal landing
Or
7. GO AROUND (GA) button PRESS, Execute Missed Approach Procedure
8. Apply GA power.
9. Set missed approach altitude in the altitude preselect.

NOTE

Pressing the GA button will not disconnect the autopilot. Select NAV or HDG mode to fly the missed approach procedure.

GPS APPROACH (LP, LNAV)

1. Navigation Source..... SELECT GPS on the CDI
2. Course Pointer VERIFY CDI set on the Desired Course

NOTE

Ensure that the current heading will result in a capture of the selected course.

3. NAV Key..... PRESS, verify GPS ARMED
4. GPS Mode..... VERIFY airplane Captures and Tracks GPS Course
5. Altitude Preselect SET to next required step down altitude
6. Missed Approach Altitude SET when in ALT mode at the MDA

At Missed Approach Point,

7. AP DISC / TRIM INT button PRESS, Continue visually for a normal landing
Or
8. GO AROUND (GA) button PRESS, Execute Missed Approach Procedure
9. Apply GA power.

NOTE

Pressing the GA button will not disconnect the autopilot. Select NAV or HDG mode to fly the missed approach procedure.

LOC BC APPROACH

1. Navigation Source..... SELECT CDI to VHF Nav
Tune and Identify an ILS station frequency
2. Course Pointer SET CDI to LOC Front Course

NOTE

Ensure that the current heading will result in a capture of the selected course.

3. NAV Key..... PRESS, verify BC ARMED
(when heading is within 75 degrees of BC course)
4. BC Mode VERIFY airplane Captures and Tracks BC Course
5. Altitude Preselect SET to next required step down altitude
6. Missed Approach Altitude SET when in ALT mode at the MDA

At Missed Approach Point:

7. AP DISC / TRIM INT button PRESS, Continue visually for a normal landing
Or
8. GO AROUND (GA) button PRESS, Execute Missed Approach Procedure
9. Apply GA power.

NOTE

Pressing the GA button will not disconnect the autopilot. Select NAV or HDG mode to fly the missed approach procedure.

VOR APPROACH

1. Navigation Source..... SELECT CDI to VHF Nav
Tune and identify the station frequency
2. Course PointerSET CDI to the Desired Course

NOTE

Ensure that the current heading will result in a capture of the selected course.

3. NAV Key..... PRESS, verify VOR ARMED
4. VOR Mode VERIFY airplane Captures and Tracks VOR Course
5. Altitude PreselectSET to next required step down altitude
6. Missed Approach AltitudeSET when in ALT mode at the MDA

At Missed Approach Point,

7. AP DISC / TRIM INT button PRESS, Continue visually for a normal landing
Or
8. GO AROUND (GA) button PRESS, Execute Missed Approach Procedure
9. Apply GA power.

NOTE

Pressing the GA button will not disconnect the autopilot. Select NAV or HDG mode to fly the missed approach procedure.

DISABLING ESP

ESP can be disabled on the G5 attitude indicator with the following procedure. ESP will default to “Enabled” on the next power cycle.

1. G5 Knob PRESS
2. ESP SELECT
3. G5 Knob PRESS

SECTION 5 – PERFORMANCE

No Change.

This page intentionally left blank.

SECTION 6 – WEIGHT AND BALANCE

No Change.

This page intentionally left blank.

SECTION 7 – SYSTEM DESCRIPTION

AFCS OVERVIEW

The GFC 500 is a digital Automatic Flight Control System (AFCS). It is a two-axis autopilot and flight director system which provides the pilot with the following features:

G5 Outputs to Autopilot — The G5 flight instrument provides attitude, rate, and acceleration information to the servos. Additionally, indicated airspeed, vertical speed, pressure altitude and GPS information are sent to the autopilot for mode control.

Flight Director (FD) — The flight director processing occurs in the G5 instrument. Selected modes for the flight director are displayed on the G5 autopilot status box.

The flight director provides:

- Command Bars showing pitch/roll guidance
- Vertical / lateral mode selection and processing

Autopilot (AP) — Autopilot operation occurs within the pitch, roll, and optional pitch trim servo. It also provides servo monitoring, and automatic flight control in response to flight director steering commands, attitude and rate information, and airspeed.

Optional Electric Pitch Trim — The pitch trim servo provides manual electric pitch trim capability when the autopilot is not engaged. The trim servo provides automatic pitch trim when the autopilot is engaged and the airplane is in the air. Automatic trim functionality is disabled on the ground.

GMC 507 — Pilot commands to the autopilot and flight director are entered through the GMC 507 autopilot mode panel. The GMC 507 contains internal sensors which calculate the aircraft attitude, attitude rate and accelerations. These inertial sensors are completely independent from the sensors within the G5 and the rest of the autopilot system, and are not used for the flight director, autopilot, trim or ESP functions. They are used solely to provide independent monitoring of the GFC 500.

Airspeed and Altitude Information — The GFC 500 requires airspeed and altitude information from the G5 instrument.

Other components of the AFCS include the GSA 28 pitch, roll, and optional pitch trim servo that also contain autopilot processors, control wheel mounted elevator trim switch (if trim servo is installed), control wheel mounted autopilot disconnect and trim interrupt button (AP DISC / TRIM INT), and a Go-Around (GA) button.

Underspeed Protection (USP) — The GFC 500 will provide Underspeed Protection when the autopilot is engaged.

When the minimum airspeed of 65 KIAS is reached, a visual MINSPD message will appear above the airspeed tape and the autopilot will lower the nose to maintain 65 KIAS. An aural “AIRSPEED, AIRSPEED” voice alert will sound for installations connected to an audio panel.

Underspeed Protection is exited automatically when airspeed exceeds 70 KIAS.

Overspeed Protection (OSP) — The GFC 500 will provide Overspeed Protection when the autopilot is engaged.

When the maximum airspeed of 165 KIAS is reached, visual MAXSPD message will appear above the airspeed tape and the autopilot will raise the nose of the aircraft to avoid exceeding the maximum configured airspeed. An aural “AIRSPEED, AIRSPEED” voice alert will sound for installations connected to an audio panel.

Overspeed Protection is exited automatically when airspeed is reduced below 160 KIAS.

Coupled Go-Around — Pressing the GA button will not disengage the autopilot. Instead, the autopilot will attempt to capture and track the flight director command bars. If insufficient airplane performance is available to follow the commands, the autopilot will enter Underspeed Protection mode at the minimum airspeed.

Electronic Stability and Protection (ESP) — The GFC 500 will provide Electronic Stability and Protection when the autopilot is not engaged.

Electronic Stability and Protection (ESP) uses the autopilot servos to assist the pilot in maintaining the airplane in a safe flight condition within the airplane's normal pitch, roll and airspeed envelopes.

Electronic Stability and Protection is invoked when the pilot allows the airplane to exceed one or more conditions beyond normal flight defined below:

- Pitch attitude beyond normal flight (+20°, -15°)
- Roll attitude beyond normal flight (45°)
- High airspeed beyond normal flight (above 176 KIAS)
- Low airspeed below normal flight (below 60 KIAS)

The conditions that are required for ESP to be available are:

- Pitch and Roll servos available
- Autopilot not engaged
- The GPS altitude above ground is more than 200 feet (for low airspeed mode)
- Aircraft is within the autopilot engagement envelope (+/-50° in pitch and +/-75° in roll)

Protection for excessive Pitch, Roll, and Airspeed is provided when the limit thresholds are first exceeded, which engages the appropriate servo in ESP mode at a nominal torque level to bring the airplane back within the normal flight envelope. If the airplane deviates further from the normal flight envelope, the servo torque will increase until the maximum torque level is reached in an attempt to return the airplane into the normal flight envelope. Once the airplane returns to within the normal flight envelope, ESP will deactivate the autopilot servos.

When the normal flight envelope thresholds have been exceeded for more than 10 seconds, ESP Autolevel Mode is activated. Autolevel Mode engages the autopilot to bring the airplane back into straight and level flight based on 0° roll angle and 0 FPM vertical speed. An aural "ENGAGING AUTOPILOT" alert (or a Sonalert tone) sounds and the Flight Director mode annunciation will indicate LVL for the pitch and roll modes.

Anytime an ESP mode is active, the pilot can interrupt ESP by using the Autopilot Disconnect (AP DISC / TRIM INT) switch, or simply override ESP by overpowering the autopilot servos. The pilot may also disable ESP through the G5 menu.

The engagement and disengagement attitude limits are displayed with double hash marks on the roll indicator depending on the airplane attitude and whether or not ESP is active in roll. When ESP is inactive (roll attitude within nominal limits) only the engagement limit indications are displayed in order to reduce clutter on the roll indicator.

Display symbology implemented for ESP is illustrated in the following figures.




Figure 7-1: Nominal Roll Attitude ESP Engagement Limit Indications

Once ESP becomes active in roll, the engagement limit indication that was crossed (either Left or Right) will move to the lower disengagement limit indication. The opposite roll limit remains at the engagement limit.




Figure 7-2: Engagement Limit Indications Upon ESP Activation

Disconnect Methods

The following conditions will cause the autopilot to automatically disconnect:

- Electrical power failure, including pulling the AUTOPILOT circuit breaker.
- Internal autopilot system failure (including internal AHRS failure).

The following pilot actions will cause the autopilot to disconnect:

- Pressing the red AP DISC / TRIM INT button on the pilot's control wheel.
- Actuating the manual electric trim switch (if installed).
- Pushing the AP Key on the GMC 507 mode controller when the autopilot is engaged.
- Pulling the AUTOPILOT circuit breaker.

The red AP DISC / TRIM INT button on the pilot's control wheel will interrupt power to the manual electric trim for as long as the switch is depressed.

AUTOPILOT CONTROL UNIT AND DISPLAY




Figure 7-3: GMC 507 Control Unit (Reference Only)



Figure 7-4: G5 Display (Reference Only)

The following tables list the available AFCS vertical and lateral modes with their corresponding controls and annunciations. The UP/DN wheel can be used to change the vertical mode reference while operating in Pitch Hold, Vertical Speed, Altitude Hold, or IAS mode. Increments of change and maximum ranges of values for each of these references using the UP/DN wheel are also listed in the table.

AFCS VERTICAL MODES

Vertical Mode	Control	Annunciation	Reference Range	Reference Change Increment
Pitch Hold	(default)	PIT	20° Nose Up 15° Nose Down	0.5°
Selected Altitude Capture	*	ALTS		
Altitude Hold	ALT Key	ALT nnnnn		10 FT
Vertical Speed	VS Key	VS nnnn	-2000 to +2000 FPM	100 FPM
IAS Hold	IAS Key	IAS nnn	65 to 165 KT	1 KT
Vertical Path Tracking (VNAV)	VNV Key	N/A		
Glidepath	APR Key	GP		
Glideslope		GS		
Takeoff or Go Around	GA Button	TO or GA	7°	
Level (LVL)	LVL Key	LVL	Zero Vertical Speed	
ESP High Pitch Engagement			ESP High Pitch Attitude engages at 20° nose up	
ESP Low Pitch Engagement			ESP Low Pitch Attitude engages at 15° nose down	
ESP High Airspeed Engagement			ESP High Airspeed engages at 176 KIAS	
ESP Low Airspeed Engagement			When above 200 FT AGL, ESP Low Airspeed engages at 60 KIAS. (This mode only available if height above terrain is available from a compatible Garmin GPS).	

* ALTS arms automatically when PIT, VS, IAS, or GA is active.

AFCS LATERAL MODES

Lateral Mode	Control	Annunciation	Maximum Roll Command Limit
Roll Mode	(default)	ROL	30°
Heading Select	HDG Key	HDG	30°
Track Select	TRK Key	TRK	30°
Navigation, GPS Arm/Capture/Track	NAV Key	GPS	30°
Navigation, VOR Enroute and Approach Arm/Capture/Track		VOR	30°
Navigation, LOC Arm/Capture/Track (No Glideslope)		LOC	30°
Backcourse Arm/Capture/Track		BC	30°
Approach, GPS Arm/Capture/Track (Glidepath Mode Automatically Armed, if available)	APR Key	GPS	30°
Approach, ILS Arm/Capture/Track (Glideslope Mode Automatically Armed)		LOC	30°
Takeoff or Go Around	GA Button	TO or GA	Wings Level
LVL (Level)	LVL Key	LVL	Wings Level
ESP Roll Attitude Engagement	ESP Roll Attitude engages at 45°		

The autopilot may be engaged within the following ranges:

Pitch 50° nose up to 50° nose down

Roll ±75°

If the above pitch or roll limits are exceeded while the autopilot is engaged, the autopilot will disconnect. Engaging the autopilot outside of its command limits, but within its engagement limits, will cause the autopilot to return the aircraft within command limits. The autopilot is capable of commanding the aircraft in the following ranges:

Pitch 20° nose up to 15° nose down

Roll ±30°

PREFLIGHT TEST

During the preflight test the G5 will display PFT in the autopilot status box. The autopilot disconnect tone sounds at the completion of the preflight test and the PFT annunciation is removed. If GFC 500 fails the PFT, a yellow AP with a red X is displayed in the autopilot status box on the G5.

MESSAGES AND ANNUNCIATIONS

Autopilot Messages	
AFCS Controller Key Stuck	The system has sensed a key input on the GMC 507 for 30 seconds or longer.
AFCS Controller Audio Database Missing	The audio database is missing from the GMC 507. The aural voice alerts will not be heard.
Servo Clutch Fault	One or more autopilot servos has a stuck clutch. The servo needs service.
Servo Trim Input Fault	The inputs to the trim system are invalid. The trim system needs service.
Autopilot Annunciations	
AFCS	Autopilot has failed. Autopilot and trim are inoperative and flight director is not available.
AP	Autopilot normal disconnect.
AP	Autopilot abnormal disconnect.
AP	Autopilot has failed. The autopilot is inoperative. FD modes may still be available.
MAXSPD	Autopilot Overspeed Protection mode is active. Autopilot will raise the nose to limit the aircraft's speed.
MINSPD	Autopilot Underspeed Protection mode is active. Autopilot will lower the nose to prevent the aircraft's speed from decreasing.
PFT	Autopilot preflight test is in progress.
PTRIM	Pitch Trim Fail – Manual Electric Pitch Trim is inoperative.
TRIM DOWN	Elevator Trim Down – Autopilot is holding elevator nose down force. The pitch trim needs to be adjusted nose down.
TRIM UP	Elevator Trim Up – Autopilot is holding elevator nose up force. The pitch trim needs to be adjusted nose up.

LIGHTING

When the aircraft's dimming bus is selected off, or full dim, GMC 507 mode control panel lighting is controlled by integrated photocells which sense the ambient cockpit lighting.